MATERIAL SAFETY DATA SHEET Barrier Coat- Radiant Barrier Latex Paint Coating:

PRODUCT NAME: BARRIER COAT #85 RADIANT BARRIER LATEX PAINT HMIS CODES: H F R P PRODUCT CODE: HT 85

DISTRIBUTOR IDENTIFICATION

DISTRIBUTOR'S NAME: UNITED COMMUNITY SERVICES OF AMERICA DISTRIBUTOR'S ADDRESS: 3002 ROUTE 23 NORTH, NEWFOUNDLAND, NJ 07435 For Emergency Assistance involving chemicals call – CHEMTREC (800) 424-9300 INFORMATION PHONE (973) 208-1122 (?) NAME OF PREPARER (?) REV V – 01/15/03 (?)

PHYSICAL/CHEMICAL CHARACTERISTICS

PRODUCT CLASS: Polymer Resin/Pigment/Water Mixture APPREARANCE AND ODOR: Gray/Aluminum, mild odor.

FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: OSHA: Nonflammable FLASH POINT: Not Applicable EXTINGUISHING MEDIA: Water spray, Carbon dioxide, Foam, Dry Chemical. UNUSUAL FIRE AND EXPLOSION HAZARDS: Not Applicable

REACTIVITY DATA

CONDITION TO AVOID: Contains Aluminum Flake, **Do Not use mechanical mixers or shakers.** Care should be taken when opening a previously used container to allow possible built-up pressure to escape (hold down lid with one hand while opening container away from yourself with the other hand). INCOMPATIBILITY (MATERIALS TO AVOID) Strong oxidizers.

HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE Vapor odors may cause irritation, nausea, headaches, and dizziness. SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE EYE CONTACT: Can cause minor irritation, redness and tearing. SKIN CONTACT: Can cause minor irritation. INGESTIONAL HEALTH RISKS AND SYMPTOMS OF EXPOSURE Can cause nausea, and gastrointestinal irritation. HEALTH HAZARDS (ACUTE AND CHRONIC) ACUTE: Excessive inhalation of vapors may cause headaches and nausea. CHRONIC: None recognized. EMERGENCY AND FIRST AID PROCEDURES EYE CONTACT: Clean eyes with plenty of water. SKIN CONTACT: Clean with soap and water. INHALATION: Move affected person to fresh air. Apply artificial respiration if necessary. Seek medical attention immediately. INGESTION: Drink water to dilute. Do not induce vomiting. Call a physician. IN CASE MATERIAL IS RELEASED OR SPILLED: Clean spills immediately with absorbent. WASTE DISPOSAL METHOD: Dispose of all waste in accordance with federal, state, and local regulations. **PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Keep containers closed when not in use. Do not store or handle neat heat, flames, and strong oxidants. Store in a cool, well ventilated area. VENTILATION: Provide sufficient ventilation.

EYE PROTECTION: Use face shield or goggles.

DISCLAIMER

The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness. Rev: 09/22/03 (?)